



Pluggable terminal blocks


Screw clamp, DIN 1-3




MA 2,5/5.CPE...




MA 2,5/5.2CPE



MA 2,5/5D2.2CPE




BAM2



FE2CPE

FEM6


BADL




FEDCP

SCF6

BJMI5




CBM...



FE1BCP

FEDBCP



COC1

BO05

MA 2,5/5.CPE... - 2,5 mm² block - 5.08 mm .200" spacing

Characteristics

		IEC NFC VDE	UL	CSA
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²	24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²		
Voltage	V	320(1)	300	300
Current	A	24/12+12	20/10+10	20/10+10
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	8.5 mm / .33"		
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in		

MA 2,5/5.2CPE... - 2,5 mm² block - 5.08 mm .200" spacing

Characteristics

		IEC NFC VDE	UL	CSA
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²	24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²		
Voltage	V	320	300	300
Current	A	24/12+12	20/10+10	20/10+10
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	10 mm / .394"		
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in		

MA 2,5/5D2.2CPE... - 2,5 mm² block - 5.08 mm .200" spacing

Characteristics

		IEC NFC VDE	UL	CSA
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²	24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²		
Voltage	V	320	300	300
Current	A	12/12	10/10	10/10
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	10 mm / .394"		
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in		

Selection

Description	Type	Order P/N	Packaging	
Standard block grey	<input type="checkbox"/>	MA 2,5/5.CPE	0115 957.12	50
Block equipped with 1 red Led 24V 4,8mA grey	<input type="checkbox"/>	MA 2,5/5.CPE-L24	0115 959.24	50
Block equipped with 1 diode 1N 4007 blue	<input type="checkbox"/>	MA 2,5/5.CPE-D	0125 960.23	50
Standard block grey	<input type="checkbox"/>	MA 2,5/5.2CPE	0115 964.11	50
Standard block blue	<input type="checkbox"/>	MA 2,5/5.2CPE	0125 711.15	50
Double deck block with 2 independant levels grey	<input type="checkbox"/>	MA 2,5/5D2.2CPE	0115 961.16	50
Double deck block with 2 independant levels blue	<input type="checkbox"/>	MA 2,5/5D2.2CPE	0125 961.10	50
Double deck block with 2 connected levels grey	<input type="checkbox"/>	MA 2,5/5D2.2CPE	0115 962.17	50


Accessories

End stop V0	light grey	BADL	9 mm	0399 903.02	(screwless)	50
		BAM2	9.9 mm	0399 967.01	(with screw)	50
End section	grey	<input type="checkbox"/>	FEM6	2.8 mm	0118 368.16	20
		<input type="checkbox"/>	FE2CPE	2.8 mm	0215 038.20	20
		<input type="checkbox"/>	FEDCP	2.54 mm	0215 071.21	20
Separator end section (for MA 2,5/5.CPE... only)	grey	<input type="checkbox"/>	SCF6	3 mm	0118 707.03	20
Assembled jumper bar with IP20 protection		BJMI5	2 poles	0176 278.16		10
		BJMI5	3 poles	0176 279.17		10
		BJMI5	4 poles	0176 280.05		10
		BJMI5	5 poles	0176 281.22		10
		BJMI5	10 poles	0176 282.23		10
Shield connector (for MA 2,5/5.CPE... only)		CBM5	0.5 mm	0168 366.16		50
		CBM8	0.8 mm	0168 367.17		50
End section-flange kit (right + left)		FE-BCP	5.08 mm	0206 391.07		10
		FE1BCP	5.08 mm	0206 389.15		10
		FEDBCP	5.08 mm	0206 392.00		10
Busbar for LED common		BO05	500 mm	0177 849.04		
Coding peg		COC1		0299 777.16		10


Ⓞ Working voltage may vary according to Led

Pluggable switch terminal blocks


Screw clamp, DIN 1-3




MA 2,5/5.SNB-CPE




MA 2,5/5-SB-CPE




MA 2,5/5-SFA-CPE



BAM2




FE2CPE




BADL



COC1



FE1BCP



BNS5



FUAUTO

MA 2,5/5.SNB-CPE - 2.5 mm² switch block - 5.08 mm .200" spacing

Characteristics

		IEC		UL	CSA
		NFC	VDE		
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²		24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²			
Voltage	V	320	300	300	
Current	A	10	10	10	
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG	
Wire stripping length	mm / inches	10 mm / .394"			
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in			

MA 2,5/5-SB-CPE - 2.5 mm² switch block - 5.08 mm .200" spacing

Characteristics

		IEC		UL	CSA
		NFC	VDE		
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²		24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²			
Voltage	V	320	300	300	
Current	A	10 ②	10(1)	10(1)	
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG	
Wire stripping length	mm / inches	10 mm / .394"			
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in			

MA 2,5/5-SFA-CPE - 2.5 mm² switch block - 5.08 mm .200" spacing

Characteristics

		IEC		UL	CSA
		NFC	VDE		
Wire size mm ² / AWG	Solid	0.2 - 4 mm ²		24-12 AWG	24-12 AWG
	Stranded	0.22 - 2.5 mm ²			
Voltage	V	320	300	300	
Current	A	3 ②	3	3	
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG	
Wire stripping length	mm / inches	10 mm / .394"			
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in			

Selection

Description	Type	Order P/N	Packaging
Heavy duty switch block with orange blade grey <input type="checkbox"/>	MA 2,5/5.SNB-CPE	0115 966.13	50
Switch block with polarized plug (delivered separately) grey <input type="checkbox"/>	MA 2,5/5-SB-CPE	0115 720.20	50
Switch block with fuse holder for Automotive Mini Fuse grey <input type="checkbox"/>	MA 2,5/5-SFA-CPE	0115 770.02	50

Accessories

End stop V0	light grey <input type="checkbox"/>	BADL	9 mm	0399 903.02	(screwless)	50
		BAM2	9.9 mm	0399 967.01	(with screw)	50
End section	grey <input type="checkbox"/>	FE2CPE	2.8 mm	0215 038.20		20
End section-flange kit (right + left)		FE1BCP	5.08 mm	0206 389.15		10
Coding peg		COC1		0299 777.16		10
Fuse plug to solder + screw (for MA 2,5/5-SB-CPE only)		BNS5		0116 702.24		50
Mini Fuse 32 V max. (for MA 2,5/5-SFA-CPE only)		FUAUTO	2 A	0179 879.14		10
		FUAUTO	3 A	0179 880.02		10

① Rated current according to fuse : 5 A max.
② Working voltage according to fuse

Female plugs

Compatible with MA 2,5/5-...CPE terminal blocks

Screw clamp

CPFT2/... - 2.5 mm² screw clamp plug - 5.08 mm .200" spacing

Characteristics

		IEC	UL	CSA
Wire size mm ² / AWG	Solid	0 - 2.5 mm ²	24-12 AWG	24-12 AWG
	Stranded	0 - 2.5 mm ²		
Voltage	V	250	300	300
Current	A	12	15	15
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	7.5 mm / .295"		
Recommended torque	Nm / lb.in	0.4 / 3.5 lb.in		

Selection

Description	Type	Order P/N	Packaging
Screw clamp plug, wire parallel to connection black ■	CPFT2/2	2 poles	0094 302.21
	CPFT2/3	3 poles	0094 303.22
	CPFT2/4	4 poles	0094 304.23
	CPFT2/5	5 poles	0094 305.24
	CPFT2/6	6 poles	0094 306.25
	CPFT2/7	7 poles	0094 307.26
	CPFT2/8	8 poles	0094 308.07
	CPFT2/9	9 poles	0094 309.00
	CPFT2/10	10 poles	0094 310.24
	CPFT2/11	11 poles	0094 311.11
	CPFT2/12	12 poles	0094 312.12
	CPFT2/13	13 poles	0094 313.13
	CPFT2/14	14 poles	0094 314.14
	CPFT2/15	15 poles	0094 315.15
	Screw clamp plug, wire perpendicular to connection black ■	CPFT2/R-2	2 poles
CPFT2/R-3		3 poles	0094 353.23
CPFT2/R-4		4 poles	0094 354.24
CPFT2/R-5		5 poles	0094 355.25
CPFT2/R-6		6 poles	0094 356.26
CPFT2/R-7		7 poles	0094 357.27
CPFT2/R-8		8 poles	0094 358.00
CPFT2/R-9		9 poles	0094 359.01
CPFT2/R-10		10 poles	0094 360.06
CPFT2/R-11		11 poles	0094 361.23
CPFT2/R-12		12 poles	0094 362.24
CPFT2/R-13		13 poles	0094 363.25
CPFT2/R-14		14 poles	0094 364.26
CPFT2/R-15		15 poles	0094 365.27

Accessories

Flange assembly R + L + M2,5 screw black ■	BCPF	axis sp. 5.08 mm	0178 072.05
Test plug	FC2	DIA. 2 mm	0007 865.26
Coding part	COCF		0199 320.04

