Mounting Brackets

360° rotation

15° adjustments

Rotating

This mounting bracket is used to provide adjustment of the sensor after mounting. Canbe surface mounted or mounted on 35mm DIN rail.

Model Number OMH4-4950

Model No.
OMH4-4950

Adjustable

This mounting bracket is used to provide adjustment of the sensor after mounting.

To order specify model number **MH4-3742**.

Model No.
MH4-3742

M4 Tap · 30 · M4 x 8 Screw · 4 · 22 · 6 · 16 · 25 · 16 · 54.66 · 12 Max. · Ø4.2

18mm Pilot Light (12-24 VDC)

This pilot light provides ultra-bright status indication for almost any industrial application including part bins, machinery, conveyor lines and error proofing. Available in red, yellow or green (or all three combined), these indicators feature an IP67,nickel-plated brass housing for harsh-duty applications.

Quick Disconnect
Male Receptable End View.

V1 Type

Yellow LED (+) — Black
Blue — (–)
Green LED (+) — Brown
White — Red LED (+)

45 · 36 · 29 · 1.0 · M12 x 1 · 24 across the flats · M18 x 1 · 4 thickness

Model Number	LED Color
LED18-RYG-P	Red, Yellow, Green
LED18-RRR-P	Red
LED18-YYY-P	Yellow
LED18-GGG-P	Green

Test Instruments

On-site troubleshooting can be a problem without the proper testing equipment. With P+F's hand-held tester, proximity sensors can be tested without having to remove the sensor from its installation. With this compact easy-to-read tester, instructions are right on the front of the unit.

You can check all 2-, 3- and 4-wire DC sensors and all 2- and 3-wire AC sensors.

If the tester is improperly connected to a sensor, a safety feature prevents damage to either the tester or the sensor.

To order specify model number **1-1350**.

Model No.
1-1350

The ST-03 is a universal, compact testing device that fits in your palm.
Features:
• The unit tests the operation of all DC sensors in 2-wire, 3-wire and 4-wire configurations, and all sensors built according to DIN 19234, NAMUR.
• Will not damage sensors that are connected incorrectly.
• Push-button terminals allow quick, easy sensor connection.

To order specify model number **ST-03**.

Model No.
ST-03

Inline Transistor Converters NPN⟷PNP

These converters are used to convert the transistor output of any standard 3-wire DC sensor from one type to the other. NPN outputs can be converted to PNP or vice versa.

Model No.
V1-G-NPN/PNP CONVERTER-V1-G
V1-G-PNP/NPN CONVERTER-V1-G

Face View (female)

Face View (male)

Color Code
1. Brown
2. Not used
3. Blue
4. Black
5. Not used

Color Code
1. Brown
2. Not used
3. Blue
4. Black
5. Not used

12.0 · 53.5 · 45.5 · 485mm

V1 (M12x1) Micro Connection