

Coils/Inductors/Transformers > Coils(SMD) > for General Use Wire Wound Type

PDF Download











'Data Sheet' contains Dimensions, Rated Value and Packaging.

**This part is obsolete that we do not accept order.
Please consult with us for details.**

Specification

Details

Status	OBSL(Orders are not accepted)
Global Part Number	LQH43MN152J01L
Previous Part Number	LQH4N152J04
Inductance	1500μH
Tolerance	±5%
Test Frequency	1kHz
Rated Current	40mA
Max. of DC resistance	37.0ohm
Avg. of DC resistance	
Q (min.)	40
Test Frequency	252kHz
Self Resonance Frequency (min.)	1.6MHz
Min. of Operating Temp.	-25°C
Max. of Operating Temp.	+85°C
Length	4.5mm
Width	3.2mm
Thickness	2.6mm
Case Size	1812
Weight (Typ.)	0.12g
Last Time Buy	March 2005
Alternatives	LQH43MN152J03L

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Q-f Characteristics\(Typ.\)](#)
-  [L-I Characteristics\(Typ.\)](#)
-  [Features](#)
-  [Notice\(Soldering and Mounting\)](#)
-  [Packaging](#)
-  [Notice \(storage and operating condition\)](#)
-  [Notice \(handling\)](#)

Minimum Quantity

180mm Paper Tape	
------------------	--

180mm Plastic Tape	500
330mm Paper Tape	
330mm Plastic Tape	
Bulk Case	
Bulk(Bag)	
Ammo Pack	
320Reel	
Magazine	
Box	

Product specifications in this catalog are as of July 2005.

UP 

| [Site Map](#) | [History](#) | [Terms of use](#) | [Privacy Policy](#) |

All Rights Reserved, Copyright© Murata Manufacturing Co., Ltd. 2005