

LC Female Connector Solder Attachment 4 Hole Flange Pin Terminal, 1.440 inch Hole Spacing



## **TECHNICAL DATA SHEET**

## PE4192

Configuration	LC Female
Connector Connector Interface Type	LC Female Pin
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight
Mount Method	4 Hole Flange
electrical Specifications	
Impedance, Ohms	50
lechanical Specifications	
Size	
Length, in [mm]	2.25 [57.15]
Width/Dia., in [mm] Height, in [mm]	2 [51]
	2 [50.8]
Weight, Ibs [g]	0.481 [218.18]
Connector	
Type	LC Female
Contact Material and Plating	Silver Brass Nickel
Body Material and Plating Dielectric Type	Brass, Nickel PTFE
compliance Certifications (visit www.Pasternack.	
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level

LC Female Connector Solder Attachment 4 Hole Flange Pin Terminal, 1.440 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



## PE4192 CAD Drawing

## LC Female Connector Solder Attachment 4 Hole Flange

Pin Terminal, 1.440 inch Hole Spacing

