


Voltage Stabilizers

Features

- Silicon Stabilizer Diodes
- Monolithic integrated analog circuits designed for small power stabilizer and limitation circuits, providing low dynamic resistance and high-quality stabilization performance as well as low noise. In the reverse direction, these devices show the behavior of forward-biased silicon diodes.
- The end of the ZTE device marked with the cathode ring is to be connected: ZTE1.5 and ZTE2 to the negative pole of the supply voltage; ZTE2.4 thru ZTE5.1 to the positive pole of the supply voltage.



94 9367

Mechanical Data

Case: DO-35 Glass Case

Weight: approx. 0.13 g

Packaging codes/options:

TR / 10k per 13 " reel (52 mm tape), 30k/box

TAP / 10k per Ammo tape, (52 mm tape), 30k/box

Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Operating Current (see Table "Characteristics")				
Inverse Current		I_F	100	mA
Power dissipation		P_{tot}	300 ¹⁾	W
Junction temperature		T_J	150	$^{\circ}\text{C}$
Storage temperature range		T_S	- 55 to + 150	$^{\circ}\text{C}$

(1) Valid provided that electrodes are kept at ambient temperature at a distance of 8 mm from case

Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Part	Symbol	Min	Typ.	Value	Unit
Temperature Coefficient of the stabilized voltage	$I_Z = 5\text{ mA}$	ZTE1.5	α_{VZ}		- 26		$10^{-4}/^{\circ}\text{C}$
		ZTE2	α_{VZ}		- 26		$10^{-4}/^{\circ}\text{C}$
		ZTE2.4	α_{VZ}		- 34		$10^{-4}/^{\circ}\text{C}$
		ZTE5.1	α_{VZ}		- 34		$10^{-4}/^{\circ}\text{C}$
Thermal resistance junction to ambient air			$R_{\theta JA}$			400 ¹⁾	$^{\circ}\text{C}/\text{W}$

(1) Valid provided that electrodes are kept at ambient temperature at a distance of 8 mm from case

Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Forward Voltage	$I_F = 10\text{ mA}$	V_F			1.1	V

Electrical Characteristics

Partnumber	Operating Voltage ⁽²⁾	Dynamic Resistance	Permissible operating current ⁽¹⁾
	$V_Z @ I_Z = 5\text{ mA}$	$r_{zj} @ I_Z = 5\text{ mA}$	$I_Z @ T_{amb} = 25\text{ }^{\circ}\text{C}$
	Ω	V	mA
			max
ZTE1.5	1.35 to 1.55	13(<20)	120
ZTE2	2.0 to 2.3	18(<30)	120
ZTE2.4	2.2 to 2.56	14(<20)	120
ZTE2.7	2.5 to 2.9	15(<20)	105
ZTE3	2.8 to 3.2	15(<20)	95
ZTE3.3	3.1 to 3.5	16(<20)	90
ZTE3.6	3.4 to 3.8	16(<25)	80
ZTE3.9	3.7 to 4.1	17(<25)	75
ZTE4.3	4.0 to 4.6	17(<25)	65
ZTE4.7	4.4 to 5.0	18(<25)	60
ZTE5.1	4.8 to 5.4	18(<25)	55

(1) Valid provided that electrodes are kept at ambient temperature at a distance of 8 mm from case

(2) Tested with pulses $t_p = 5\text{ ms}$

Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)




Figure 1. Admissible Power Dissipation vs. Ambient Temperature




Figure 2. Dynamic resistance vs. operating current, normalized




Figure 3. Dynamic resistance vs. operating voltage





Figure 4. Breakdown Characteristics



18230


Figure 5. Breakdown Characteristics

Package Dimensions in mm (Inches)

technical drawings according to DIN specifications

94 9366

Standard Glass Case
54 A 2 DIN 41880
JEDEC DO 35





Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design
and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.